



## Signature™/MC

### Ultra High Speed Floor Finish

The floor finish solution for “wet look” appearance throughout your establishment—for floor care that’s simply brilliant

#### Excellent Performance

- Unsurpassed “wet look” gloss
- Dramatic response to propane, battery and electric equipment
- Designed to excel on vinyl composite, sheet vinyl and terrazzo flooring

#### Easy to Use

- Easy to apply, thin or full coats, fast drying
- Apply over virtually any finish after deep-scrubbing with JohnsonDiversey UHS™/MC Cleaner and green pads

#### Designed For

- RETAIL
- SUPERMARKETS
- HEALTHCARE
- OFFICE
- GOVERNMENT
- EDUCATION



## Use Overview:

**Signature™/MC Ultra High Speed Floor Finish** provides unsurpassed “wet look” gloss, excellent durability and dirt release. It is easy to apply and maintain.

### Preparation

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- Strip floors using a JohnsonDiversey brand stripper per the instructions on the stripper label.

### Coating

- Apply 3 or more medium coats of product using a clean finish mop or the **JohnsonDiversey ProSpeed™/MC Finish Applicator System**. Apply additional coats until desired gloss is obtained.
- Allow 30–45 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24 hours before burnishing.

### Maintenance

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended JohnsonDiversey brand cleaner according to the label directions.
- Burnish using appropriate pads.

### Recoating

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended JohnsonDiversey brand cleaner according to the label directions.
- Blockade area and apply 1–2 uniform coats of finish using a clean mop.
- Allow finish to cure for 24 hours before burnishing.



**Signature™/MC Ultra High Speed Floor Finish** meets the newest and most stringent VOC standards in North America, including those adopted by the California Air Resources Board (CARB) 2011 regulations. In addition, SIGNATURE Floor Finish is formulated with readily biodegradable surfactants and solvents. Also, SIGNATURE Floor Finish is not formulated with any endocrine-disrupting plasticizers, dyes, or fragrances. These attributes, combined with numerous others, make this product an excellent choice for your facility under a sustainable facility care program.

## Product Specifications:

<b>Dry Time</b>	30–45 minutes (under normal conditions)
<b>Non-volatile Solids</b>	20% minimum

<b>Shelf Life</b>	2 years
<b>Slip Resistance</b>	Meets ASTM D2047 requirements for slip resistance

This product is not regulated by W.H.M.I.S. For additional information please refer to the product Material Safety Data Sheet (MSDS).

## Two convenient sizes:

PRODUCT CODE	DESCRIPTION	DILUTION
5104950	1 x 5 gallon / 18.9 L Envirobox™/MC	Ready-To-Use
4971947	6 x 2.64 / 2.5 L ProSpeed™/MC BIB (Bag-in-Box)	Ready-To-Use

## Hazard Rating:

HMS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

## Safety Reminder:

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDSs are available online at [www.johnsondiversev.com](http://www.johnsondiversev.com) or by calling 1-800-558-2332.