



High Noon^{TM/MC}

Ultra Durable Urethane Fortified UHS Floor Finish

A high solids UHS floor finish for floors that demand excellent gloss and durability

Excellent Performance

- Built with tough all-acrylic polymers and fortified with urethane for unmatched durability
- Burnishes to a rich deep gloss
- Reduces labor costs by extending recoat and strip-out cycles
- Retains good looks longer between burnishings
- Maintains clarity and color better than finishes that contain styrenated polymers

Designed For

RETAIL

HEALTHCARE

OFFICE

GOVERNMENT

EDUCATION



Use Overview:

High Noon™/MIC Ultra Durable Urethane Fortified UHS Floor Finish gives you high-gloss brilliance and durability in fewer coats, saving you time and labor.

Preparation

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- Strip floor using any **Diversey** stripper per the instructions on the stripper label.

Coating

- Apply 3 or more medium coats of **High Noon™/MIC Ultra Durable Urethane Fortified UHS Floor Finish** using a clean mop or the **JohnsonDiversey ProSpeed™/MIC Floor Finish Applicator System**. Apply additional coats until desired gloss is obtained. On porous resilient or stone floors, seal first with 2 coats of recommended **Diversey** sealer.
- Allow 30–45 minutes of drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24 hours before burnishing.

Maintenance

- Dust mop or sweep. Clean the floor daily with a mop or an automatic scrubber using the recommended **Diversey** brand cleaner according to label directions.
- To enhance appearance, burnish using the appropriate pads.



- Clean and restore gloss with recommended **Diversey** cleaner. Apply using an autoscrubber or damp mop, let floor dry and then burnish.

Recoating

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended **Diversey** cleaner according to label directions.
- Blockade area and apply 1–2 uniform coats of finish using a clean finish mop.
- Allow finish to cure for 24 hours before burnishing.

Product Specifications:

Color/Form	Opaque white, liquid
pH	8.3
Scent	Characteristic

Shelf Life	2 years
Specific Gravity	1.031

Available items:

PRODUCT CODE	DESCRIPTION/PACKAGE SIZE	DILUTION
5104829	1 x 5 gallon / 18.9 L Envirobox™/MIC	Ready-To-Use
4972051	6 x 2.5 L / 2.64 Qt. ProSpeed™/MIC BIB (Bag-in-Box)	Ready-To-Use
4003110	4 x 1 gallon / 3.78 L Containers	Ready-To-Use

Hazard Rating:

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

Safety Reminder:

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available online at www.johnsondiversey.com or by calling 888 352 2249.

For additional information, please contact:

800 558 2332 • www.johnsondiversey.com