



## **Amplify<sup>TM/MC</sup>** High Solids Durable Finish

# A high solids UHS floor finish for floors that demand excellent gloss and durability

### Excellent Performance

- One coat has the gloss of two coats
- Applies easily and levels perfectly with no mop drag
- Great mark resistance and durability

### Easy to Use

- Install up to five coats in one night
- Excellent repairability with spray buffing and burnishing
- Low odor finish is ideal for 24-hour facilities

### *Designed For*

RETAIL  
HEALTHCARE  
OFFICE  
GOVERNMENT  
EDUCATION



## Use Overview:

**Amplify™/MC High Solids Durable Finish** gives you high-gloss brilliance and durability in fewer coats, saving you time and labor.

### Preparation

- Always barricade area to be finished.
- Before the first application of **Amplify™/MC High Solids Durable Finish**, remove all old finish with recommended **Diversey** stripper.

### Coating

- Apply 3 or more medium coats of **Amplify™/MC High Solids Durable Finish** with a clean finish mop. Let dry to the touch between coats (about 30 minutes).
- On porous resilient or stone floors, seal first with 2 coats of recommended **Diversey** seal.

### Maintenance

- Clean Daily: Dust mop. Then wet clean with recommended **Diversey** cleaner in an autoscrubber or with a damp mop.
- Spray buff as needed with recommended **Diversey** spray buff, a red or beige pad and a 175–1500 RPM machine. Or burnish with a UHS pad and a battery, cord electric or propane machine at 1500–2000+ RPM.



- Clean and restore gloss with recommended **Diversey** burnisher. Apply recommended **Diversey** burnisher using an autoscrubber or damp mop, let floor dry and then burnish.

### Recoating

- Clean thoroughly. Dust mop. Machine scrub with a floor machine or autoscrubber using a blue pad and the recommended **Diversey** cleaner at the recommended dilution. Rinse well and let dry.
- Apply 2 new coats of **Amplify™/MC High Solids Durable Finish**.

## Product Specifications:

Color/Form	White liquid
pH	7.9–8.5
Scent	Bland

Shelf Life	2 years
Specific Gravity	1.03

## Available items:

PRODUCT CODE	DESCRIPTION/PACK SIZE	DILUTION
5104714	1 x 5 gallon / 18.9 L Envirobox™/MC	Ready-To-Use
4972034	1 x 2.5 L / 2.64 Qt. ProSpeed™/MC BIB (Bag-in-Box)	Ready-To-Use
4385110	4 x 1 gallon / 3.78 L Containers	Ready-To-Use

## Hazard Rating:

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

## Safety Reminder:

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available online at [www.johnsondiversey.com](http://www.johnsondiversey.com) or by calling 888 352 2249.

For additional information, please contact:

800 558 2332 • [www.johnsondiversey.com](http://www.johnsondiversey.com)