Radiance

High Gloss 25

25% Floor Finish



DESCRIPTION

This product is designed for the professional floor crew that needs a finish that will require fewer coats and still give the high gloss demanded in today's markets. Using a special polymer-resin-wax ratio, it provides superior initial gloss with unsurpassed durability. As few as two coats are needed for most applications. The finish dries to a clear film that will not yellow over time.

DIRECTIONS

- 1. Strip floor entirely of old finish using one of our recommended floor strippers.
- 2. Apply finish using a clean finish mop or applicator. As few as 2 or up to 5 coats may be applied per application. Allow 30 45 minutes for finish to dry completely before recoating.
- 3. Maintain floor by dust mopping and damp mopping as needed.
- Restore floor by damp mopping thoroughly with our recommended cleaner and buffing (175 - 2000 RPM) using our recommended spray buff or mop on restorer.

IF USING THIS PRODUCT ON CONCRETE, TERRAZZO, MARBLE, OR GRANITE: It is recommended that two coats of sealer be used to seal floor, followed by 2 - 5 coats of finish. Restore and maintain floor as normal.

RECOMMENDED PADS FOR BUFFING OR BURNISHING:

175 - 1500 RPM: Soft White or Red pad.

1500 - 2000 RPM: White, Champagne, or Light Natural.

KEEP FROM FREEZING

APPLICATIONS

For areas where stripping or spray buffing can be regularly performed such as:

- Schools and hospitals
- · Airports and offices

BENEFITS

- High solids--requires fewer coats/less labor
- Durable
- Excellent off-the-mop gloss
- Easy to maintain
- Will not yellow

SPECIFICATIONS

Color	w n i t e
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	8.60
% Non-volatile solids	2 5 %
Coverage	2000 sq. ft./gal.

PACKAGING

ITEM #	SIZE
10079818	5 gal.
10079819	4/1 gal.

MADE IN U.S.A. | HECHO EN EEUU.



