

Radiance

High Gloss 20

20% Floor Finish



DESCRIPTION

This product is a premium floor finish offering high off the mop gloss in as little as 3 - 5 coats. Utilizing the latest polymer technology, this product is extremely durable. High hardness properties reduce maintenance by controlling scuffing and scratching. Floors may be maintained by dust mopping or damp mopping with a neutral pH cleaner. Buff or burnish as desired. Ideal for use in areas where recoating time is limited and maximum durability and gloss are desired. Recommended for use on vinyl, vinyl composition, and other resilient floors.

DIRECTIONS

1. Strip floor entirely of old finish using one of our recommended floor strippers.
2. Apply finish using a clean finish mop. Apply 3 - 5 coats per application. Allow 30 - 45 minutes for finish to dry completely before recoating.
3. Allow at least 2 hours after final coat dries before burnishing. **NOTE:** When possible, it is always recommended to wait 24 hours before burnishing.
4. Maintain floor by dust mopping and spot mopping as needed.

KEEP FROM FREEZING

APPLICATIONS

Recommended for areas where low maintenance is desired:

- Schools and office buildings
- Hospitals

BENEFITS

- High solids--requires fewer coats/less labor
- Hard, durable
- Excellent off-the-mop gloss
- Will not yellow

SPECIFICATIONS

Color.....White
Fragrance.....Characteristic
pH Range.....8.0 - 8.5
Dilution.....R T U
Density.....8.55
% Non-volatile solids.....20 %
Coverage.....2000 sq. ft./gal.

PACKAGING

ITEM #	SIZE
10079823	5 gal.
10079824	4/1 gal.
10079825	55 gal.

MADE IN U.S.A. | HECHO EN EEUU.



Distributed by:



POLLOCK

1 Pollock Place, Grand Prairie, TX 75050
800.843.7320 · www.pollock.com