



New and  
Improved Formula



## Vectra® Floor Finish

# A floor finish that saves time, while giving floors diamond-like brilliance, clarity and durability

### Excellent Performance

- Diamond-like clarity and gloss
- Cures on the floor faster than traditional floor coatings
- Resists dirt embedment, black heel marks, scratching and scuffing
- Versatile finish responds well to 175–1500 RPM equipment

### Improved Formulation

- Provides better buff response
- Reduced VOCs of 54.4% and significantly decreased odors
- Now compliant with California 2010 VOC requirements
- Easier to apply—less mop drag for more consistent results

### Easy to Use

- Responds well to 175—1500 RPM equipment

### Designed For

EDUCATION

RETAIL

HEALTHCARE

OFFICE

GOVERNMENT



## Use Overview:

**Vectra® Floor Finish** provides diamond-like brilliance, clarity and long-lasting performance, saving you time and labor, while giving the brilliant appearance you demand on your floors.

- Blockade areas to be stripped or finished. Position wet-floor signs around area to be cleaned.
- Strip floor using recommended JohnsonDiversey brand stripper according to label directions.
- Apply 2–3 uniform coats using a clean mop. If higher gloss is desired, apply additional coats.
- Allow 30 minutes drying time between coats.

### Maintenance

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended JohnsonDiversey brand cleaner following label directions.
- If desired, spray buff using recommended JohnsonDiversey brand floor maintainer to enhance gloss.

### Before Recoating

- Dust mop or sweep.
- Deep scrub floor using JohnsonDiversey cleaner according to label directions.
- Apply 1–2 coats using a clean mop.

## Product Specifications:

<b>Color/Form</b>	Opaque off-white, liquid
<b>Drying Time</b>	20–30 minutes (under normal conditions)
<b>Non-volatile Solids</b>	19.0% minimum

<b>Scent</b>	Ammonia
<b>Shelf Life</b>	2 years
<b>Slip Resistance</b>	0.5 minimum (ASTM D2047)

## Four convenient sizes:

PRODUCT CODE	DESCRIPTION/PACKAGE SIZE	DILUTION
5105047	1 x 5 gallon / 18.9 L Envirobox™/MIC	Ready-To-Use
4971921	6 x 2.5 L / 2.64 Qt. ProSpeed™/MIC BIB (Bag-in-Box)	Ready-To-Use
04078	4 x 1 gallon / 3.78 L Containers	Ready-To-Use
04074	1 x 55 gallon / 208 L Drum	Ready-To-Use

## Hazard Rating:

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

## Safety Reminder:

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available online at [www.johnsondiversev.com](http://www.johnsondiversev.com) or by calling 888 352 2249.



### Removal

- Remove using recommended JohnsonDiversey brand stripper according to label directions.

### Best Results

- Do not dilute.
- Do not use on surfaces colder than 50° F (10° C).
- To avoid contamination, do not return unused product to original container.

**Note:** Floors will be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and foreign materials. Meets ASTM D2047 requirements for slip resistance.

For additional information, please contact:

800 558 2332 • [www.johnsondiversev.com](http://www.johnsondiversev.com)