



## Safety Data Sheet

Copyright, 2014, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	10-2821-6	<b>Version Number:</b>	26.00
<b>Issue Date:</b>	07/21/14	<b>Supersedes Date:</b>	06/18/12

### SECTION 1: Identification

#### 1.1. Product identifier

Scotchgard™ Spot Remover and Upholstery Cleaner

#### Product Identification Numbers

ID Number	UPC
70-0711-6295-5	00-48011-14003-7

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Carpet Care

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Commercial Solutions Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Aerosol: Category 1.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Flame | Health Hazard |

##### Pictograms



**Hazard Statements**

Extremely flammable aerosol.

Causes damage to organs:  
blood or blood-forming organs |  
cardiovascular system |

Causes damage to organs through prolonged or repeated exposure:  
blood or blood-forming organs |

**Precautionary Statements**

**General:**

Keep out of reach of children.

**Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Do not breathe mist/vapors/spray.  
Do not eat, drink or smoke when using this product.  
Wash thoroughly after handling.

**Response:**

IF exposed: Call a POISON CENTER or doctor/physician.  
Specific treatment (see Notes to Physician on this label).  
Get medical advice/attention if you feel unwell.

**Storage:**

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.  
Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Notes to Physician:**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**2.3. Hazards not otherwise classified**

Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.  
5% of the mixture consists of ingredients of unknown acute oral toxicity.  
7% of the mixture consists of ingredients of unknown acute dermal toxicity.  
7% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
WATER	7732-18-5	60 - 90 Trade Secret *
PETROLEUM GASES, LIQUEFIED, SWEETENED	68476-86-8	3 - 7 Trade Secret *
2-BUTOXYETHANOL	111-76-2	1 - 5 Trade Secret *
SODIUM OLEYLMETHYLTAURIDE	137-20-2	0.5 - 1.5 Trade Secret *
2,5-Furandione, telomer with ethenylbenzene and (1-methylethyl)benzene, ammonium salt	52720-34-0	0.5 - 1.5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade

secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. Get medical attention.

#### Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or

commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
2-BUTOXYETHANOL	111-76-2	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
2-BUTOXYETHANOL	111-76-2	OSHA	TWA:240 mg/m3(50 ppm)	Skin Notation

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Gloves made from the following material(s) are recommended:

Butyl Rubber

Neoprene

Nitrile Rubber

**Respiratory protection**

None required.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

<b>General Physical Form:</b>	Liquid Aerosol
<b>Specific Physical Form:</b>	Aerosol
<b>Odor, Color, Grade:</b>	Clear water white liquid.
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	8.9 - 9.5
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	> 212 °F
<b>Flash Point</b>	No flash point
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Density</b>	<i>No Data Available</i>
<b>Specific Gravity</b>	0.99 - 1.05 [ <i>Ref Std: WATER=1</i> ]
<b>Solubility in Water</b>	Complete
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	<i>No Data Available</i>
<b>Volatile Organic Compounds</b>	< 7 % weight [ <i>Test Method: calculated per CARB title 2</i> ]
<b>Percent volatile</b>	60 - 100 %
<b>VOC Less H2O &amp; Exempt Solvents</b>	800 - 850 g/l [ <i>Test Method: calculated per CARB title 2</i> ]

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat  
Sparks and/or flames

**10.5. Incompatible materials**

Strong oxidizing agents  
Strong acids

**10.6. Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause target organ effects after inhalation.

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause target organ effects after ingestion.

#### Target Organ Effects:

##### Single exposure may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

##### Prolonged or repeated exposure may cause:

Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE > 50 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
PETROLEUM GASES, LIQUEFIED, SWEETENED	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
2-BUTOXYETHANOL	Dermal	Rabbit	LD50 400 mg/kg
2-BUTOXYETHANOL	Inhalation-Vapor (4 hours)	Rat	LC50 2.2 mg/l
2-BUTOXYETHANOL	Ingestion	Rat	LD50 560 mg/kg
SODIUM OLEYLMETHYLTAURIDE	Ingestion	Rat	LD50 1,700 mg/kg

2,5-Furandione, telomer with ethenylbenzene and (1-methylethyl)benzene, ammonium salt	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
---	-----------	--	--

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
PETROLEUM GASES, LIQUEFIED, SWEETENED		No significant irritation
2-BUTOXYETHANOL	Rabbit	Irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
PETROLEUM GASES, LIQUEFIED, SWEETENED		No significant irritation
2-BUTOXYETHANOL	Rabbit	Severe irritant

**Skin Sensitization**

Name	Species	Value
2-BUTOXYETHANOL	Guinea pig	Not sensitizing

**Respiratory Sensitization**

Name	Species	Value

**Germ Cell Mutagenicity**

Name	Route	Value
PETROLEUM GASES, LIQUEFIED, SWEETENED	In Vitro	Not mutagenic
2-BUTOXYETHANOL	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
2-BUTOXYETHANOL	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
2-BUTOXYETHANOL	Dermal	Not toxic to development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-BUTOXYETHANOL	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	during organogenesis
2-BUTOXYETHANOL	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
PETROLEUM GASES, LIQUEFIED, SWEETENED	Inhalation	cardiac sensitization	Causes damage to organs	similar compounds	NOAEL Not available	
PETROLEUM GASES, LIQUEFIED, SWEETENED	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
PETROLEUM GASES, LIQUEFIED, SWEETENED	Inhalation	respiratory irritation	All data are negative		NOAEL Not available	
2-BUTOXYETHANOL	Dermal	endocrine system	Some positive data exist, but the data are not sufficient for	Rabbit	NOAEL 902 mg/kg	6 hours

			classification			
2-BUTOXYETHANOL	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 72 mg/kg	not available
2-BUTOXYETHANOL	Dermal	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 451 mg/kg	6 hours
2-BUTOXYETHANOL	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
2-BUTOXYETHANOL	Inhalation	blood	May cause damage to organs	Multiple animal species	NOAEL Not available	not available
2-BUTOXYETHANOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-BUTOXYETHANOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-BUTOXYETHANOL	Ingestion	blood	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
2-BUTOXYETHANOL	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
PETROLEUM GASES, LIQUEFIED, SWEETENED	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	
2-BUTOXYETHANOL	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
2-BUTOXYETHANOL	Dermal	endocrine system	All data are negative	Rabbit	NOAEL 150 mg/kg/day	90 days
2-BUTOXYETHANOL	Inhalation	blood	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.12 mg/l	90 days
2-BUTOXYETHANOL	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.4 mg/l	14 weeks
2-BUTOXYETHANOL	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.15 mg/l	14 weeks
2-BUTOXYETHANOL	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 1.9 mg/l	8 days
2-BUTOXYETHANOL	Ingestion	blood	Causes damage to organs through prolonged or repeated exposure	Multiple animal species	NOAEL Not available	not available
2-BUTOXYETHANOL	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available

**Aspiration Hazard**

Name	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material



and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations. Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

#### 311/312 Hazard Categories:

Fire Hazard - Yes    Pressure Hazard - Yes    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
2-BUTOXYETHANOL (GLYCOL ETHERS)	111-76-2	1 - 5

### 15.2. State Regulations

### 15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

## 15.4. International Regulations

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None  
**Aerosol Storage Code:** 1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health:** \*2 **Flammability:** 3 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

<b>Document Group:</b>	10-2821-6	<b>Version Number:</b>	26.00
<b>Issue Date:</b>	07/21/14	<b>Supersedes Date:</b>	06/18/12

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)